

# Lecture on UNIX-like operating systems

Daniel Bosk<sup>1</sup>

Department of Information Technology and Media (ITM),  
Mid Sweden University, Sundsvall.

unix.tex 537 2012-12-28 00:06:27Z danbos

---

<sup>1</sup>This work is licensed under the Creative Commons Attribution-ShareAlike 3.0 Unported license. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/>.

# Overview

## 1 The History of UNIX

- The development of UNIX
- Evolution of UNIX

## 2 UNIX Architecture

- Architectural overview

### 3 UNIX Shell

- Bourne Shell
- Shell Scripting

# Overview

- 1 The History of UNIX
  - The development of UNIX
  - Evolution of UNIX
- 2 UNIX Architecture
  - Architectural overview
- 3 UNIX Shell
  - Bourne Shell
  - Shell Scripting

# Development timeline

## The 1960s

1965 Multiplexed Information and Computing Service (MULTICS) was a joint effort between MIT, Bell Labs and GE to

*“develop a convenient, interactive, useable computer system that could support many users.” [Lab02a]*

- 1969
- Bell Labs withdrew from the project, but Ken Thompson, Dennis Ritchie, Douglas McIlroy, and J. F. Ossanna continued on their own.
  - Started to write the system on a PDP-7, at first simply as a file system.
  - The system then got a shell, an editor, and an assembler. [Lab02a]

# Development timeline

## The 1960s

1965 Multiplexed Information and Computing Service (MULTICS) was a joint effort between MIT, Bell Labs and GE to

*“develop a convenient, interactive, useable computer system that could support many users.” [Lab02a]*

- 1969
- Bell Labs withdrew from the project, but Ken Thompson, Dennis Ritchie, Douglas McIlroy, and J. F. Ossanna continued on their own.
  - Started to write the system on a PDP-7, at first simply as a file system.
  - The system then got a shell, an editor, and an assembler. [Lab02a]

# Development timeline

## The 1970s

- 1970
  - Brian Kernighan suggests the name UNIX.
  - They port the current code to a PDP-11.
  - Focused for use in text-processing, patent applications for Bell Labs.
- 1971 Ritchie improved Thompson's B programming language into the C programming language.
- 1972 Thompson started rewriting UNIX in C. (And continuous improvement of C.) [Lab02a]

# Development timeline

## The 1970s

- 1970
  - Brian Kernighan suggests the name UNIX.
  - They port the current code to a PDP-11.
  - Focused for use in text-processing, patent applications for Bell Labs.
- 1971 Ritchie improved Thompson's B programming language into the C programming language.
- 1972 Thompson started rewriting UNIX in C. (And continuous improvement of C.) [Lab02a]

# Development timeline

## The 1970s

- 1970
  - Brian Kernighan suggests the name UNIX.
  - They port the current code to a PDP-11.
  - Focused for use in text-processing, patent applications for Bell Labs.
- 1971 Ritchie improved Thompson's B programming language into the C programming language.
- 1972 Thompson started rewriting UNIX in C. (And continuous improvement of C.) [Lab02a]



## Development timeline

## The 1970s, continued

- 1973
  - UNIX completely rewritten in C.
  - Thompson added McIlroy's concept of pipes. With this came the UNIX philosophy:

[Lab02a]

# Development timeline

## The 1970s, continued

1973

- UNIX completely rewritten in C.
- Thompson added McIlroy's concept of pipes. With this came the UNIX philosophy:

*"Write programs that do one thing and do it well. Write programs to work together.*

*Write programs that handle text streams, because that is a universal interface."*

*[Lab02a]*

- Ritchie took initiative to manual pages, McIlroy soon took over and is the mind behind the layout of manual pages. [Lab02a]

## Development timeline

## The 1970s, continued

1973

[Lab02a]

- Ritchie took initiative to manual pages, McIlroy soon took over and is the mind behind the layout of manual pages. [Lab02a]

# Development timeline

## The 1970s, continued

- 1975 Thompson is visiting professor at University of California-Berkeley (UCB). While there he developed version 6 of UNIX.
- 1978 Professors at Berkeley continued the enhancement of UNIX and distributed their work as Berkeley Software Distribution (BSD). [Lab02a]

# Development timeline

## The 1970s, continued

- 1975 Thompson is visiting professor at University of California-Berkeley (UCB). While there he developed version 6 of UNIX.
- 1978 Professors at Berkeley continued the enhancement of UNIX and distributed their work as Berkeley Software Distribution (BSD). [Lab02a]

# Development timeline

## The 1980s

- 1983
- Sockets API added to BSD (4.2BSD), i.e. TCP/IP made easily available.
  - David Korn develops the Korn Shell scripting language.
  - Bjarne Stroustrup develops the first version of C++.

1984 AT&T, owner of Bell Labs, started selling UNIX-licenses to companies. [Lab02a]

# Development timeline

## The 1980s

- 1983
- Sockets API added to BSD (4.2BSD), i.e. TCP/IP made easily available.
  - David Korn develops the Korn Shell scripting language.
  - Bjarne Stroustrup develops the first version of C++.
- 1984 AT&T, owner of Bell Labs, started selling UNIX-licenses to companies. [Lab02a]

# Development timeline

## Present

To this day, UNIX-like operating systems operate “most large Internet servers, businesses and universities, and a major part of academic and industrial research in operating systems is based on UNIX” [Lab02a].



# Evolution of UNIX




Image: [https://en.wikipedia.org/wiki/File:Unix\\_history-simple.svg](https://en.wikipedia.org/wiki/File:Unix_history-simple.svg).

For details see <http://www.levenez.com/unix/>.

# Overview

- 1 The History of UNIX
  - The development of UNIX
  - Evolution of UNIX
- 2 UNIX Architecture
  - Architectural overview
- 3 UNIX Shell
  - Bourne Shell
  - Shell Scripting

# Architectural overview

Layered approach:

- ① hardware,
- ② monolithic kernel (drivers, system calls),
- ③ shell,
- ④ tools and application programs, and
- ⑤ users. [?, See]Figure 2.11, page 60]Silberschatz2005osc

Features:

- time-sharing,
- portability [Lab02b], and
- *everything is a file.*

# Architectural overview

Layered approach:

- ① hardware,
- ② monolithic kernel (drivers, system calls),
- ③ shell,
- ④ tools and application programs, and
- ⑤ users. [?, See]Figure 2.11, page 60]Silberschatz2005osc

Features:

- time-sharing,
- portability [Lab02b], and
- *everything is a file.*

# Architectural overview

## Different types of kernels




Image: <https://en.wikipedia.org/wiki/File:OS-structure2.svg>.

# Architectural overview

## Kernels of different UNIX-like and UNIX-based systems

OpenBSD uses a monolithic kernel and the layered structure of the classical UNIX.

FreeBSD uses a monolithic kernel but has added kernel modules.

Linux uses a monolithic kernel with loadable kernel modules.

MacOS X uses a hybrid between monolithic kernel and microkernel.

During your advanced study assignment you will go more in-depth on this subject.

# Architectural overview

## Kernels of different UNIX-like and UNIX-based systems

OpenBSD uses a monolithic kernel and the layered structure of the classical UNIX.

FreeBSD uses a monolithic kernel but has added kernel modules.

Linux uses a monolithic kernel with loadable kernel modules.

MacOS X uses a hybrid between monolithic kernel and microkernel.

During your advanced study assignment you will go more in-depth on this subject.

# Architectural overview

## Kernels of different UNIX-like and UNIX-based systems

OpenBSD uses a monolithic kernel and the layered structure of the classical UNIX.

FreeBSD uses a monolithic kernel but has added kernel modules.

**Linux** uses a monolithic kernel with loadable kernel modules.

MacOS X uses a hybrid between monolithic kernel and microkernel.

During your advanced study assignment you will go more in-depth on this subject.



# Architectural overview

## Kernels of different UNIX-like and UNIX-based systems

OpenBSD uses a monolithic kernel and the layered structure of the classical UNIX.

FreeBSD uses a monolithic kernel but has added kernel modules.

Linux uses a monolithic kernel with loadable kernel modules.

MacOS X uses a hybrid between monolithic kernel and microkernel.

During your advanced study assignment you will go more in-depth on this subject.

# Architectural overview

## Kernels of different UNIX-like and UNIX-based systems

OpenBSD uses a monolithic kernel and the layered structure of the classical UNIX.

FreeBSD uses a monolithic kernel but has added kernel modules.

Linux uses a monolithic kernel with loadable kernel modules.

MacOS X uses a hybrid between monolithic kernel and microkernel.

During your advanced study assignment you will go more in-depth on this subject.

# UNIX File System Structure

The UNIX design is to have everything represented as a file in the file system.

/	The root directory.
/bin	Fundamental user utilities.
/dev	Device files (refers to actual physical devices).
/etc	Configuration files.
/home	User home directories.
/sbin	System programs and administration utilities fundamental to the system.
/usr	The majority of user utilities.
/var	Data files used by system programs, e.g. logs.

For further details see `hier(7)` [`bsd`, `lin`].

# UNIX File System Structure

The UNIX design is to have everything represented as a file in the file system.

/	The root directory.
/bin	Fundamental user utilities.
/dev	Device files (refers to actual physical devices).
/etc	Configuration files.
/home	User home directories.
/sbin	System programs and administration utilities fundamental to the system.
/usr	The majority of user utilities.
/var	Data files used by system programs, e.g. logs.

For further details see `hier(7)` [`bsd`, `lin`].

# UNIX File System Structure, continued

<code>/usr/bin</code>	Common utilities, programming tools, and applications.
<code>/usr/include</code>	Standard C include files.
<code>/usr/X11R6</code>	Files required for the X window system.
<code>/usr/lib</code>	System libraries used by programs in <code>/usr/bin</code> .
<code>/usr/src</code>	The source code for the system.

For further details see man-page `hier(7)` [`bsd`, `lin`].

# Overview

- 1 The History of UNIX
  - The development of UNIX
  - Evolution of UNIX
- 2 UNIX Architecture
  - Architectural overview
- 3 UNIX Shell
  - Bourne Shell
  - Shell Scripting

# UNIX Shell

- The simplistic and modular design of UNIX makes many different shells available, e.g.
  - Korn Shell (ksh),
  - Bourne Shell (sh),
  - Bourne Again Shell (bash), and
  - the X window system (X11R6).
- The shell interprets commands from the user and executes them.
  - The UNIX design of the shell is to implement all commands as separate programs – *which does one thing and does it well*.
  - This way commands can easily be added or removed.
  - The programs are located in /bin, /sbin, /usr/bin, etc.
  - Standard shells are located in /bin.

# UNIX Shell

- The simplistic and modular design of UNIX makes many different shells available, e.g.
  - Korn Shell (ksh),
  - Bourne Shell (sh),
  - Bourne Again Shell (bash), and
  - the X window system (X11R6).
- The shell interprets commands from the user and executes them.
  - The UNIX design of the shell is to implement all commands as separate programs – *which does one thing and does it well*.
  - This way commands can easily be added or removed.
  - The programs are located in /bin, /sbin, /usr/bin, etc.
  - Standard shells are located in /bin.



# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Bourne Shell

- Environment variables accessible from shell and programs.
- Looks for simple commands in directories named in PATH environment variable.
- The two special and always open files: stdin and stdout.
  - stdin input from e.g. keyboard connected to terminal.
  - stdout output from process to e.g. display.
- Redirections:
  - > redirects stdout to a named file.
  - < reads contents of file as stdin.
- The pipe: redirects stdout of one process to stdin of another.

# Shell Scripting

- Just shell commands, redirections, pipes etc. written to a file.
- Thanks to the UNIX design, there is no difference reading from stdin with stdin being the keyboard and stdin being redirected from a file.
- The file is hence read by the shell process and executed.



# Shell Scripting

- Just shell commands, redirections, pipes etc. written to a file.
- Thanks to the UNIX design, there is no difference reading from stdin with stdin being the keyboard and stdin being redirected from a file.
- The file is hence read by the shell process and executed.

# Shell Scripting

- Just shell commands, redirections, pipes etc. written to a file.
- Thanks to the UNIX design, there is no difference reading from stdin with stdin being the keyboard and stdin being redirected from a file.
- The file is hence read by the shell process and executed.

# References I



*OpenBSD Reference Manual.*

OpenBSD 5.0.



Bell Labs.

The creation of the UNIX operating system, 2002.



Bell Labs.

An overview of the UNIX operating system, 2002.



*Linux Programmer's Manual.*